

# MQ Series Manual Quad Drive Carton Sealer

The BestPack® MQ Series are designed to meet your light to heavy weight carton closure applications. The MQ Series uniquely uses 4 belt drives, two on the side and two on the top, in order to drive the carton with more power and stability.

All systems incorporate our exclusive pop out pressure sensitive "High Speed" tape heads with patented tab adjustment, and an extra 4" carton height extension on the upper assembly.



# Key Points of the Carton Sealer

**Operator Fed** 

**Uniform Cartons** 

**Top & Bottom Seal** 

### **Features**

- Designed for Uniform Applications
- Four Belts 2 Top & 2 Side
- Adjustable Bed Height from MQ22 & MQ44: 20.5" to 30"
- Electrical on/off box can be mounted on either side of carton sealer
- Width/Height Adjustment on either side of carton sealer
- Carton Top Compression Unit
- Tape Roll Lengths: 1000 yd., 1500 yd., 2000 yd.
- Heavy Duty Frame
- UL Approved Electrical Parts
- Rugged Construction
- Capable of Interchanging 2" or 3" Tape Heads
- Fully Adjustable

# **Options**

- Spare Parts Kit
- High Speed Motor Upgrade (Up to 125 ft.)
- Heavy-Duty Locking Casters
- Infeed/Exit Conveyor
- Motorized Height and/or Width Adjustment
- Interlock Safety GatesStainless Steel

**CBM** SYSTEMS INC

Distributed by CBM Systems, Inc.

#### +1 (909) 670-8888 | sales@cbmsystem.com | www.cbmsystem.com

 $\ensuremath{\textcircled{O}}$  2016 BestPack Packaging Systems. All rights reserved.

## **Extra Accessories to Improve Efficiency**



#### Spare Parts Kit

- High Speed Motor Upgrade (Up to 125 ft.)
- Carton Sealing Tape
- Stainless Steel
- Short Infeed/Exit Conveyor w/L-Bracket



Long Infeed/Exit Conveyor w/ L-Bracket



Spare Tape Head

#### **Machine & Carton Specifications**

#### 110 Volts 60 Hz

Power Requirements

#### Up to 50 Cartons/min.

Locking Casters

Speed

**None** Air Requirements 420 - 600 lbs

Shipping Weight

Model	Machine Dimensions Length × Width × Height	Carton Range* Length (min max.) x Width (min max.) x Height (min max.)	Conveyor Height Adjustment Height (min max.)	Cartons per min.	Shipping Weight (Ibs.)
MQ22-2 or 22-3 2" or 3" Tape Head	(39.5") x (36.0") x (55.5")	(6.0" - U) x (7.5" - 21.0") x (4.5" - 20.5")	(20.5" - 30")	Up to 40	420
MQ22-2H or 22-3H <b>2" or 3" Tape Head</b>	(39.5") × (36.0") × (55.5")	(6.0" - U) x (7.5" - 21.0") x (4.5" - 20.5")	(20.5" - 30")	Up to 50	420
MQ23-2 or 23-3 2" or 3" Tape Head	(39.5") x (36.0") x (68.0")	(6.0" - U) x (7.5" - 21.0") x (4.5" - 30.0")	(20.5" - 30")	Up to 40	420
MQ23-3H or 23-3H 2" or 3" Tape Head	(39.5") x (36.0") x (68.0")	(6.0" - U) x (7.5" - 21.0") x (4.5" - 30.0")	(20.5" - 30")	Up to 50	420
MQ33-3 3" Tape Head	(39.5") x (43.0") x (81.0")	(6.0" - U) x (7.5" - 30.0") x (6.0" - 30.0")	(20.5" - 30")	Up to 25	542
MQ33-3H <b>3" Tape Head</b>	(39.5") x (43.0") x (81.0")	(6.0" - U) x (7.5" - 30.0") x (6.0" - 30.0")	(20.5" - 30")	Up to 32	542
MQ44-3 <b>3" Tape Head</b>	(39.5") x (53.0") x (91.0")	(6.0" - U) x (7.5" - 40.0") x (6.0" - 40.0")	(20.5" - 30")	Up to 25	600
MQ44-3H <b>3" Tape Head</b>	(39.5") x (53.0") x (91.0")	(6.0" - U) x (7.5" - 40.0") x (6.0" - 40.0")	(20.5" - 30")	Up to 32	600

Information subject to change without notice.

© 2016 BestPack Packaging Systems. All rights reserved.



CBM Systems, Inc. 1599 Monte Vista Avenue Claremont, CA 91711 sales@cbmsystem.com (909) 670-8888 www.cbmsystem.com



U - Unlimited