

RQ Series

Random Quad Drive Carton Sealer

The BestPack® RQ Series SemiAutomatic Random Tape Carton Sealers are built for speed and rugged dependability. The 4 belt carton sealer system is a solution for heavy-duty applications. This heavy duty workhorse is ideal for those rugged and random sealing applications

All systems incorporate our exclusive pop out pressure sensitive "High Speed" tape heads with patented tab adjustment available in both 2" or 3". All our machines are also available in stainless steel.



Key Points of the Carton Sealer







Top & Bottom Seal

Features

- Handles Random Carton Sizes
- Adjustable Bed Height from RQ22 & RQ33: 20.5" 30"

RQ44: 24.5" - 30"

- 4 Belts 2 Top and 2 Side
- Extra 4" Carton Height Adjustment Available on Upper Assembly
- Height Sensors
- Tape Roll Lengths: 1000 yd., 1500 yd., 2000 yd.
- Heavy Duty Frame
- UL Approved Electrical Parts
- Rugged Construction
- Capable of Interchanging 2" or 3" Tape Heads
- Electrical on/off box can be mounted on either side of the Carton Sealer

Options

- Spare Parts Kit
- High Speed Motor Upgrade (Up to 125 ft.)
- Locking Heavy-Duty Casters
- Interlock Safety Gates
- · Low or No Tape Sensor
- Infeed/Exit Conveyor w/Stabilizer
- Random Side Compression Rollers



Extra Accessories to Improve Efficiency









Spare Parts Kit

Locking Casters

Long Infeed/Exit Conveyor w/ L-Bracket

Spare Tape Head

• High Speed Motor Upgrade (Up to 125 ft.)

- Carton Sealing Tape
- Stainless Steel

Machine & Carton Specifications

110 Volts 60 Hz

Power Requirements

Up to 15 Cartons/min.

Speed (2" Carton Sealer)

90 - 100 PSI

6 - 8 CFM Air Requirements 632-657 lbs

Shipping Weight

| Model | Machine Dimensions Length × Width × Height | Carton Range* Length (min max.) x Width (min max.) x Height (min max.) | Conveyor Height Adjustment Height (min max.) | Cartons per min. | Shipping Weight (lbs.) |
|---------------------------------|---|--|---|---------------------|---------------------------|
| RQ22-2 2" Tape Head | (42.8") x (34.6") x (57.5") | (7.0" - U) x (7.5" - 21.0") x (4.5" - 20.0") | (20.5" - 30") | Up to 15 | 632 |
| RQ22-3 3" Tape Head | (42.8") × (34.6") × (57.5") | (7.0" - U) x (7.5" - 21.0") x (4.5" - 30.0") | (20.5" - 30") | Up to 15 | 632 |
| RQ23-2 2" Tape Head | (42.8") × (34.6") × (57.5") | (7.0" - U) x (7.5" - 21.0") x (4.5" - 30.0") | (20.5" - 30") | Up to 13 | 657 |
| RQ23-3 3" Tape Head | (42.8") × (34.6") × (57.5") | (7.0" - U) x (7.5" - 21.0") x (4.5" - 30.0") | (20.5" - 30") | Up to 13 | 632 |
| RQ EC 33-3 2" Tape Head | (42.87") x (45.0") x (76.0") | (7.0" - U) x (7.5" - 30.0") x (4.5" - 30.0") | (20.5" - 30") | Up to 13 | 657 |
| RQ33-3-CP** 3" Tape Head | (42.87") x (46.0") x (76.0") | (7.0" - U) x (7.5" - 30.0") x (6.0" - 30") | (20.5" - 30") | Up to 13 | 657 |
| RQ44-3** 3" Tape Head | (46.3") × (54.7") × (86.0") | (7.0" - U) x (7.5" - 40.0") x (6.0" - 40.0") | (24.5" - 30") | Up to 12 | 657 |

Information subject to change without notice.

**Includes Random Top Side Compression Rollers & Interlock Safety Gates
© 2016 BestPack Packaging Systems. All rights reserved.

U - Unlimited High Speed Option Available



