

## RS Bottom Only

### Random Bottom Only Sealer

The BestPack™ RS20 Series is a Semi-Automatic Random Bottom Carton Sealer designed to fulfill light to heavy duty random bottom sealing needs. This unit is incredibly effective when random bottom carton sealing volume has become too large for hand sealing.

Our RS20 line incorporates our exclusive 2" or 3" pop-out pressure-sensitive "High Speed" tape heads with BestPack's patented tab adjustment. All BestPack units are available in our standard baked enamel finish and food-grade 304 stainless steel.



## Key Points of the Carton Sealer



Operator Fed



Random Cartons



Bottom Seal

## Features

- Handles Random Carton Sizes
- Side Belt Drive
- Adjustable Bed Height from 20.5" - 30"
- Exclusive Pop-out pressure sensitive "high speed" tape head with patented tab adjustment and noise reduction arm
- Tape Roll Lengths: 1000 yd., 1500 yd., 2000 yd.
- Maintenance Free Oil-less Cylinders
- Heavy Duty Frame
- UL Approved Electrical Parts
- Electrical on/off box can be mounted on either side of the carton sealer
- Tool Kit & Operation Manual

## Options

- Spare Parts Kit
- High Speed Motor Upgrade (Up to 125 ft. per min.)
- Locking Heavy-Duty Casters
- Infeed/Exit Conveyor w/L-Bracket Stabilizer
- Interlock Safety Gates
- Low or No Tape Sensor
- Stainless Steel

# Extra Accessories to Improve Efficiency



Spare Parts Kit



Locking Casters



Long Infeed/Exit Conveyor  
w/ L-Bracket



Spare Tape Head

- High Speed Motor Upgrade (Up to 125 ft. per min.)
- Short Infeed/Exit Conveyor w/L-Bracket Stabilizer
- Stainless Steel
- Carton Sealing Tape

## Machine & Carton Specifications

**110 Volts 60 Hz**  
Power Requirements

**Up to 15 Cartons/min.**  
Speed

**80 PSI, 5 SCFM**  
Air Requirements

**330-380 lbs**  
Shipping Weight

Model	Machine Dimensions Length x Width x Height	Carton Range*			Conveyor Height Adjustment Height (min. - max.)	Cartons per min.	Shipping Weight (lbs.)
		Length (min. - max.)	Width (min. - max.)	Height (min. - max.)			
RS20-2 <b>2" Tape Head</b>	(42.9") x (30.0") x (28.8")	(6.0" - U)	(4.25" - 20.0")	(4.0+)"	(20.5" - 30.0")	Up to 15	318
RS20-3 <b>3" Tape Head</b>	(42.9") x (30.0") x (28.8")	(6.0" - U)	(5.25" - 21.0")	(4.0+)"	(20.5" - 30.0")	Up to 15	318
RS30-2 <b>2" Tape Head</b>	(42.9") x (39.4") x (28.8")	(6.0" - U)	(4.5" - 30.0")	(4.0+)"	(20.5" - 30.0")	Up to 15	380
RS30-3 <b>3" Tape Head</b>	(42.9") x (39.4") x (28.8")	(6.0" - U)	(5.5" - 30.0")	(4.0+)"	(20.5" - 30.0")	Up to 15	380

Information subject to change without notice.  
© 2016 BestPack Packaging Systems. All rights reserved.

\*Outside Dimensions Only  
U - Unlimited  
All Models available in High Speed & Stainless Steel



CBM Systems, Inc.  
1599 Monte Vista Avenue  
Claremont, CA 91711  
sales@cbmsystem.com  
(909) 670-8888  
www.cbmsystem.com

