

RSBFT Series

Random Sidedrive Bottom Flap Folder

The BestPack RSBFT Series is a random operator-fed, bottom carton sealer designed to reduce the time required to fold & seal the bottom flaps of a carton. This unit can be used when random size carton forming volume has become too large to manually form and tape the cartons, but the volume is too small to justify a fully automatic carton erector/sealer.



Our RSBFT line incorporates our exclusive 2" or 3" pop-out pressure-sensitive "High Speed" tape heads with BestPack's patented tab adjustment. All BestPack units are available in our standard baked enamel finish and food-grade 304 stainless steel.

Key Points of the Carton Sealer



Operator Fed



Random Cartons



Bottom Seal

Features

- Handles Random Carton Sizes
- Two Side Belts
- Bottom Seal Only
- Random Bottom Flap Folder
- "T" Rail with Bottom Major Flap Folding Horns
- The unit reduces operator fatigue and increases output.
- Compared to hand taping, the quality of the seal and the appearance of the carton is greatly improved.
- Adjustable Bed Height from 23.5" to 30.0"
- Tape Roll Lengths: 1000 yd., 1500 yd., & 2000 yd.
- Heavy Duty Frame
- UL Approved Electrical Parts
- Capable of Interchanging 2" or 3" Tape Heads

- Exclusive Pop-out pressure sensitive "high speed" tape head with patented tab adjustment and noise reduction arm
- Maintenance Free Oil-less Air Cylinders
- High Speed Motors
- Operation Manual

Options

- Stainless Steel
- Spare Parts Kit
- Exit Conveyors
- Locking Castors w/ Support Brackets

Extra Accessories to Improve Efficiency



Spare Parts Kit

- Carton Sealing Tape



Locking Casters
w/Support Brackets



Long Exit Conveyor



Spare Tape Head

Machine & Carton Specifications

110 Volts 60 Hz
Power Requirements

Up to 10 Cartons/min.
Speed

60-80 PSI
5 SCFM (Dry Air)
Air Requirements

350 lbs
Shipping Weight

Model	Machine Dimensions Length x Width x Height	Carton Range* Length (min. - max.) x Width (min. - max.) x Height (min. - max.)	Conveyor Height Adjustment Height (min. - max.)	Cartons per min.	Shipping Weight (lbs.)
RSBFT20-2H** 2" Tape Head	(95.9") x (35.5") x (29.4")	(7.8" - 23.6") x (7.8" - 19.6") x (4.0+)"	(23.5" - 30.0")	Up to 10	350
RSBFT20-3H** 3" Tape Head	(95.9") x (35.5") x (29.4")	(7.8" - 23.6") x (7.8" - 19.6") x (4.0+)"	(23.5" - 30.0")	Up to 10	350

Information subject to change without notice.
© 2016 BestPack Packaging Systems. All rights reserved.

* Outside Dimensions Only
** High Speed



CBM Systems, Inc.
1599 Monte Vista Avenue
Claremont, CA 91711
sales@cbmsystem.com
(909) 670-8888
www.cbmsystem.com

